



GATOR ROCK BOND - LIQUID BINDER AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 03/01/2018

TECHNICAL DATA SHEET

- Update:** January 3, 2018
Make sure you have an updated data sheet on hand.
Canada and U.S. dial 1-855-847-7767 or (450) 624-1611
- Description:** Mixed **GATOR ROCK BOND** with 100% washed and dried riverstone, creates a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.
- Ideal For:**
- Banding, edging and trimming.
 - Pathways.
 - Walkways.
 - Tree wells.
- Features:**
- Porous & permeable.
 - Keeps stones in place.
 - Reduce maintenance & clean up.
 - Durable in extreme conditions.
 - Solvent-free.
 - High elongation.
 - Shock absorption.
 - Easy to apply and easy to repair.
 - Superb U.V. and weathering resistance.
- Installation instructions:**
- TYPES OF ROCK THAT CAN BE USED WITH GATOR ROCK BOND:
GRANITE - LIMESTONE - MARBLE (1/8" TO 3/8")
THESE ROCKS HAVE TO BE CLEAN, FREE OF DUST & 100% DRY.**
- METHOD of application of **GATOR ROCK BOND:**
1. Prepare a solid base by densely compacting 4" (10 cm) of crushed stones.
 2. Mix in a ratio of one container (1 US gal.) of GATOR ROCK BOND with (320 lbs) of the above mentioned stones for 4 minutes. Mix products automatically with a masonry mixer or you can manually mix on a sheet of plywood or in a wheel barrow.
 3. Trowel the mixed riverstone on the surface desired, within 20 minutes after mixing.
- Please note:**
- For pedestrian use only.
 - Works above 60°F (16°C).
 - Allow 24 hours to dry without rain.
- Coverage:** 1 US gal mixed with 320 lbs of dry stone will cover 80 sq. ft. (7.4 sq. m.). The size of the stone are to be between 1/8" & 3/8" for a minimum 1/2" surface thickness.
- Storage:** Store in a cool, dry, well ventilated area. Store in upright position. Store at above freezing temperature 32°F (0°C). Shelf life is 1 year in original unopened container.
- Warning!** Refer to material safety data sheet for further information. Toxic if swallowed. Avoid ingestion or eye contact. Avoid contact with strong alkalines or acids.





**GATOR ROCK BOND - LIQUID BINDER AGENT
KEEPS STONES IN PLACE**

TDS Revision Date (dd/mm/yyyy): 03/01/2018

First Aid Ingestion: Call physician or Poison control centre immediately. Do not induce vomiting unless directed to do so by medical personnel. Eye Contact: Flush contaminated area with water for 15 minutes. Consult a physician if necessary.

Packaging:	Product	Size	per Box	per Pallet
	Gator Rock Bond- Liquid Binding Agent	3.78 L (1 U.S. gal.)	4 units	24 boxes

WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface and sub-surface preparation and product application. **ALLIANCE DESIGNER PRODUCTS INC.** agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then **ALLIANCE DESIGNER PRODUCTS INC.** agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC. IN ALL EVENTS, **ALLIANCE DESIGNER PRODUCTS INC.**, SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, **ALLIANCE DESIGNER PRODUCTS INC.**, EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com