



GATOR WETCAST NATURAL LOOK ZERO GLOSS SEALER SIGNATURE SERIES FOR WET CAST PRODUCTS

TDS Revision Date (dd/mm/yyyy): 13/04/2016

TECHNICAL DATA SHEET

Update: April 13, 2016
 Make sure you have an updated data sheet on hand.
 Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description: **SIGNATURE GATOR SEAL FOR WET CAST** products is made from fluorochemical polymers. This sealer penetrates deep into the Wet Cast products thus reducing the oil and dirt penetration, as well as protecting them from the corrosion of de-icing salt.

Features:

- Easier to clean and maintain
- Water-based, zero gloss
- Works at above 32°F (0°C)
- Natural look
- Can be applied on damp surface
- Rain-safe after 24 hours

Helps resist:

- Corrosion from de-icing salt
- Effects from UV rays
- Motor oil and grease stains

Coverage:

- 1 u.s. gal. (3.78 l) Coverage 175 sq. ft. (16m²)
- 5 u.s. gal. (18.9 l) Coverage 875 sq. ft. (80m²)

For use on: For Wet Cast products

PLEASE NOTE

1. Wet Cast products should only be sealed 60 days after their installation date. Consult Wet Cast products manufacturer's for their recommendation.
2. Wet Cast products and jointing sand MUST be 100% dry.
3. Temperature should be between 32°F (0°C) and 85°F (29°C) when sealer is applied.
4. Wet Cast product surface must be cool to the touch when sealer is applied (between 32°F (0°C) and 85°F (29°C)).
5. First clean Wet Cast products with Gator Clean products. Remove all oil, grease and rust stains.
6. First clean natural stones with Gator Clean products. Remove all oil, grease and rust stains.
7. Use Gator Efflorescence Cleaner to remove any trapped efflorescence. It also thoroughly cleans the surface to ensure a proper sealer adhesion.
8. Use just one (1) layer of sealer.
9. Signature Series Wet Cast Sealer can be applied on dry or damp surfaces.
10. Specifically formulated to be used on unsealed surfaces only. Cannot be used as a resealer.
11. Wear protective gloves, eye protection and respiratory protection.

APPLICATION INSTRUCTIONS

1. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
2. Remove all the stains from the Wet Cast products, using Gator Clean products. Use Gator Clean Sealer Stripper to remove any unknown coating that remains on the Wet Cast product surface.
3. Remove all contaminated jointing material and replace with Gator Polymeric Sand. Follow the instructions on the back of the bags for proper sand installation.
4. Wait at least 48 hours at a minimum temperature of 32°F (0°C) and no rain for the Gator Polymeric Sand to properly harden.



GATOR WETCAST NATURAL LOOK ZERO GLOSS SEALER SIGNATURE SERIES FOR WET CAST PRODUCTS

TDS Revision Date (dd/mm/yyyy): 13/04/2016

APPLICATION INSTRUCTIONS (CONT.):

5. Clean the entire surface with the Gator Efflorescence Cleaner. This product will remove the efflorescence trapped in the natural stone pores as well as thoroughly clean the surface for proper sealer adhesion .
6. Wait at least 48 hours at a minimum temperature of 32°F (0°C) and no rain so the sand & natural stone surface are dry.
7. Best Practice: (See online video. 2 people needed.) Apply one (1) coat of Signature Series Wet Cast Sealer using a sprayer in 60 sq. ft. sections, then use a solvent-resistant foam roller to remove the excess sealer left on the surface.
8. Signature Series Wet Cast Sealer is water repellent, rain safe, after 90 min
9. Let the sealer dry for 24 hours before using the sealed area.

Alliance Designer Products shall not be liable for any non-compliant use.

Coating Category: Low Solids Coatings. VOC Concentration Limits: <5 g/L (grams of VOC per liter of material). SCAQMD compliant.


Packaging:	Product	Size	Per Box	Per Pallet
	GATOR SEAL SIGNATURE WET CAST NATURAL LOOK	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR SEAL SIGNATURE WET CAST NATURAL LOOK	18.9 L (5 U.S. gal.)		48 pails

LIMITED WARRANTY:

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4m²) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4m²). Alliance Designer Products Inc. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation Alliance Designer Products Inc. is to refund the purchase price. Proof of purchase is required for any claim. Alliance Designer Products Inc. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, Alliance Designer Products Inc. excludes any implied warranty of quality, merchantability or fitness for purpose.

***The container must at all times be stored at above 32°F (0°C) to receive the benefit under the Limited Warranty.**

Keep out of reach of children. Mild eye and skin irritant. Avoid inhaling vapor or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Flush with running water after use. Avoid mixing with other chemicals. If swallowed, call the poison control center nearest you.



SEE THE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM