



GATOR RESEALER
FOR DRY CAST CONCRETE PAVERS
TDS Revision Date (dd/mm/yyyy): 25/04/2016

Page 1 of 2



TECHNICAL DATA SHEET

- Update:** April 25, 2016
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **GATOR SEAL RESEALER** for concrete pavers is made from acrylic based polymers. Gator Seal Resealer will penetrate the formula of the existing sealer and reactivate the molecules to create a rejuvenated seal to protect the concrete paver surface. Thus reducing the penetration of oil and dirt, as well as protecting them from de-icing salt.
- Features:**
- Easier to clean and maintain
 - Solvent based.
 - Can be applied over Gator Wet Look and Satin Look sealers
 - Film former
 - Rejuvenates surface
- Helps resist:**
- Corrosion from de-icing salt
 - Effects from UV rays
 - Motor oil and grease stains
- Coverage:**
- 1 u.s. gal. (3.78 l) covers 175 ft² (16m²)
 - 5 u.s. gal. (18.9 l) covers 875 ft² (80m²)
- For use on:** For dry cast concrete pavers
- Please note:**
- 1) Concrete pavers should only be sealed 60 days after their installation date. Consult concrete paver manufacturer's for their recommendation.
 - 2) Concrete pavers & jointing sand **MUST** be 100% dry.
 - 3) Temperature should be between 60°F / 16°C to 85°F / 29°C when sealer is applied.
 - 4) Concrete paver surface temperature should be between 60°F / 16°C to 85°F / 29°C and concrete paver surface must be cool to the touch when sealer is applied.
 - 5) GATOR EFFLORESCENCE CLEANER to remove ground in dirt from the surface of concrete pavers. It will make the concrete pavers look clean and vibrant. Applying Gator Efflorescence Cleaner before a Gator Seal Resealer application will assure you of a deeper penetration into the cleaned surface.
 - 6) Just use 1 layer of GATOR SEAL RESEALER.
 - 7) When using Gator Seal Resealer assure yourself at least 48 hours of dry conditions prior to applying Gator Seal Resealer. If temperature is above 60°F / 15°C the surface should dry within hours.
 - 8) Wear protective gloves, eye protection and respiratory protection.

APPLICATION INSTRUCTIONS:

- 1) ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
- 2) Before commencing the project ensure that there is no rain forecasted for the next 24 hours.
- 3) First clean concrete pavers with Gator Clean products. Remove all oil, grease and rust stains. Use Gator Efflorescence Cleaner to thoroughly cleans the surface to ensure a proper Gator Seal Resealer adhesion.
- 4) Wait at least 48 hours at a minimum temperature of 60°F / 15°C and no rain so the Gator Polymeric sand & concrete paver surface are dry.



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



GATOR RESEALER
FOR DRY CAST CONCRETE PAVERS
 TDS Revision Date (dd/mm/yyyy): 25/04/2016



APPLICATION INSTRUCTIONS CONTINUED:

- 5) Apply coat of Gator Seal Resealer using a foam roller.
- 6) Gator Resealer is water repellent, rain safe, after 90 min.
- 7) Let it dry for 24 hours before using the sealed area.

This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.

Coating Category: Low Solids Coatings. VOC Concentration Limits: <120 g/L (grams of VOC per liter of material).

Packaging:	Product	Size	per Box	per Pallet
	GATOR SEAL RESEALER	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR SEAL RESEALER	18.9 L (5 U.S. gal.)		48 pails

LIMITED WARRANTY:


Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 32°F (0°C) and away from direct sun to receive the benefit under the Limited Warranty.

Keep out of the reach of children. Contains: Xylene (CAS # 1330-20-7).

DANGER! FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN IRRITANT. Inhalation may cause irritation. May also affect the brain and nervous system causing dizziness, headache or nausea. Contains material which may cause liver and kidney damage. Possible developmental hazard – contains material which may adversely affect the developing fetus, based on animal data. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Wear protective gloves, eye protection and respiratory protection. Do not swallow. Wash thoroughly after handling. Replace cap after use. Keep away from heat, sparks, and open flame. Do not smoke, extinguish all flames and pilot lights, and turn off other sources of ignition during use and until all vapors are gone. FIRST AID: If swallowed, call a physician or Poison Control Center immediately. Do not induce vomiting. If in eyes, immediately rinse with water for at least 15 minutes and get medical attention. In case of skin contact, wash thoroughly with mild soap and running water. Remove contaminated clothing. If breathed in, move person to fresh air. Call a physician.



DANGER
 POISON IRRITANT FLAMMABLE



SEE THE INSTALLATION VIDEO
 ON ALLIANCEGATOR.COM



Alliance Designer Products Inc.
 225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com