



GATOR SEALER SIGNATURE SERIES FOR WET CAST PRODUCTS LOW GLOSS

TDS Revision Date (dd/mm/yyyy): 18/08/2016

TECHNICAL DATA SHEET

- Update:** August 18, 2016
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **SIGNATURE GATOR SEAL FOR WET CAST PRODUCTS** is made from acrylic-based polymers. Signature Gator Seal for Wet Cast products penetrates deep into the Wet Cast products, thus reducing the oil and dirt penetration, as well as protecting them from the corrosion of de-icing salt. Specifically formulated to be used on unsealed surfaces only.
- Features:**
- Easier to clean and maintain
 - Low gloss
 - Film former
 - Subtle color enhancer
 - Joint Stabilizer
 - Rain-safe after 90 min.
- Helps resist:**
- Corrosion from de-icing salt
 - Effects from UV rays
 - Motor oil and grease stains
- Coverage:**
- 1 u.s. gal. (3.78 l) covers 175 ft² (16 m²)
 - 5 u.s. gal. (18.9 l) covers 875 ft² (80 m²)
- For use on:** For Wet Cast products
- Please note:**
1. Wet Cast products should only be sealed 60 days after their installation date. Consult Wet Cast product manufacturer's for their recommendation.
 2. Wet Cast products and jointing sand MUST be 100% dry.
 3. Temperature should be between 60°F (16°C) and 85°F (29°C) when sealer is applied.
 4. Wet Cast product surface must be cool to the touch when sealer is applied (between 60°F (16°C) and 85°F (29°C)).
 5. First clean Wet Cast products with Gator Clean products. Remove all oil, grease and rust stains.
 6. Use Gator Efflorescence Cleaner to remove any trapped efflorescence. It also thoroughly cleans the surface to ensure a proper sealer adhesion.
 7. Use just one (1) layer of sealer.
 8. When using Gator Seal, assure yourself at least 48 hours of dry conditions prior to applying the sealer.
 9. Specifically formulated to be used on unsealed surfaces only. Cannot be used as a resealer.
 10. Wear protective gloves, eye protection and respiratory protection.
- Application instructions:**
- 1) ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectation.
 - 2) Remove all the stains from the Wet Cast products, using Gator Clean products. Use Gator Clean Sealer Stripper to remove any unknown coating that remains on the surface of Wet Cast products.
 - 3) Remove all contaminated jointing material and replace with Gator Polymeric Sand. Follow the instructions on the back of the bags for proper sand installation.
 - 4) Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain for the Gator Polymeric Sand to properly harden.
 - 5) Clean the entire surface with the Gator Efflorescence Cleaner. This product will remove the efflorescence trapped in the Wet Cast product pores as well as thoroughly clean the surface for proper sealer adhesion.



Signature SERIES



GATOR SEALER SIGNATURE SERIES FOR WET CAST PRODUCTS LOW GLOSS

TDS Revision Date (dd/mm/yyyy): 18/08/2016

Application instructions (cont.):

- 6) Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain so the sand & Wet Cast product surface are dry.
- 7) Best Practice: (See online video. 2 people needed.) Apply one (1) coat of Gator Seal using a sprayer in 60 sq. ft. sections, then use a solvent-resistant foam roller to remove the excess sealer left on the surface.
- 8) Signature Series Wet Cast Sealer is water repellent, rain safe, after 90 min.
- 9) Let the sealer dry for 24 hours before using the sealed area.

This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.

Coating Category: Low Solids Coatings. VOC Concentration Limits: <120 g/L (grams of VOC per liter of material). Compliant to SCAQMD.

Packaging:	Product	Size	per Box	per Pallet
	GATOR SEAL SIGNATURE WET CAST LOW GLOSS	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR SEAL SIGNATURE WET CAST LOW GLOSS	18.9 L (5 U.S. gal.)		48 pails

LIMITED WARRANTY:

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 32°F (0°C) and away from direct sun to receive the benefit under the Limited Warranty.

Keep out of the reach of children. Contains: Xylene (CAS # 1330-20-7).

DANGER! FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. SKIN IRRITANT. Inhalation may cause irritation. May also affect the brain and nervous system causing dizziness, headache or nausea. Contains material which may cause liver and kidney damage. Possible developmental hazard – contains material which may adversely affect the developing fetus, based on animal data. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Wear protective gloves, eye protection and respiratory protection. Do not swallow. Wash thoroughly after handling. Replace cap after use. Keep away from heat, sparks, and open flame. Do not smoke, extinguish all flames and pilot lights, and turn off other sources of ignition during use and until all vapors are gone. FIRST AID: If swallowed, call a physician or Poison Control Center immediately. Do not induce vomiting. If in eyes, immediately rinse with water for at least 15 minutes and get medical attention. In case of skin contact, wash thoroughly with mild soap and running water. Remove contaminated clothing. If breathed in, move person to fresh air. Call a physician.



DANGER
POISON IRRITANT FLAMMABLE

SEE THE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com