



**GATOR STONE BOND & XP
FOR PATHWAYS, PATIOS AND WALKWAYS**
TDS Revision Date (dd/mm/yyyy): 02/07/2019

TECHNICAL DATA SHEET

Update: July 2, 2019
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description: **GATOR STONE BOND AND XP** are a unique blend of acrylic polymers designed to bind together a wide variety of small aggregates commonly referred to as decomposed granites (dg): pathway mixes, crusher runs, coarse sand, etc.

Features: **GATOR STONE BOND XP** is sold in Canada and USA.
GATOR STONE BOND is only sold in the following states:
California, Nevada, Texas, Arizona

- Easy one-coat process.
- Creates a strong bond on a wide variety of aggregates.
- Resists surface erosion from both rain water and foot traffic.

Benefits:

- Ready to use right out of the container.
- Easy to apply, one-coat application.
- Reduces dust, gravel migration and erosion.
- Allows for the use of patio/pathway year round.
- No special tools or skills required to build.
- Build using local aggregates.
- Will not harm plants or aquatic life.
- EPA-compliant.

Installation instructions:

- AGGREGATE SELECTION FOR FINAL SURFACE:** Select an aggregate that contains a variety of sizes. For instance, crushed stone mixes such as 3/8 minus, 1/4 minus or 3/16 minus work well with **GATOR STONE BOND** or **GATOR STONE BOND XP**, whereas single size aggregates like 3/8 rock or pea gravel are not suitable. Screenings with extremely high fine content are not suitable either. To ensure compatibility of selected aggregate with **GATOR STONE BOND** or **GATOR STONE BOND XP**, prepare a test area.
 - STRUCTURAL STONE BASE PREPARATION:** Before starting the actual project, factors such as climate, native soil type and amount of use, should be taken into consideration. As a rule of thumb, "The better the base preparation, the better the results."
Option 1 - For optimum performance, install 4 to 6 in of 3/4 minus crushed stone, then compact using a vibratory plate compactor.
Option 2 - Install 2 to 4 in of 3/4 minus or 3/8 minus, 1/4 minus or 3/16 minus crushed stone, then compact using a vibratory plate compactor. In restricted areas where a compactor will not fit, use a hand tamper.
- SURFACE AGGREGATE:** Spread a maximum of 1 in surface aggregate over the compacted structural stone base. Rake or screed to the desired level, a minimum slope of 2 degrees to allow water runoff. Do not compact until after **GATOR STONE BOND** or **GATOR STONE BOND XP** has been applied.



**GATOR STONE BOND & XP
FOR PATHWAYS, PATIOS AND WALKWAYS**
TDS Revision Date (dd/mm/yyyy): 02/07/2019

Installation instructions (cont.):


2. **GATOR STONE BOND** or **GATOR STONE BOND XP**: using a watering can or pump sprayer, apply the **GATOR STONE BOND** or **GATOR STONE BOND XP** to the surface at the rate of 15 sq ft per gallon for residential pedestrian use, or 10 sq ft per gallon for commercial pedestrian use. Allow **GATOR STONE BOND** or **GATOR STONE BOND XP** to fully penetrate through the material
3. **COMPACTION**: While surface is still damp but not saturated, compact the surface with a vibratory plate compactor; 2 or 3 passes are recommended. In restricted areas where a compactor will not fit, use a hand tamper. The better the compaction, the better the results.

Instructions for rebuilding AN EXISTING SURFACE

1. Scarify or rototill at least 2.5 cm (1 in) of the surface, break up any clumps, make any necessary repairs, and add new surface aggregate as needed.
2. Apply **GATOR STONE BOND** or **GATOR STONE BOND XP** at the rate of 15 sq ft (1.4 sq. m.) per gallon; allow liquid to penetrate.
3. Compact using a vibratory plate compactor. In restricted areas where a compactor will not fit, use a hand tamper.

Instructions for maintaining AN EXISTING SURFACE:

1. Make repairs as needed.
2. Apply **GATOR STONE BOND** or **GATOR STONE BOND XP** at the rate of 20 to 45 sq ft (1.9 to 4.2 sq. m.) per gallon. Some judgement will be needed, as consideration for absorption and desired results should be taken into account.
3. Compact any loose areas.



RESIDENTIAL OR COMMERCIAL PEDESTRIAN USE

IMPORTANT

- **GATOR STONE BOND** or **XP** are not sealers, we do not recommend using it as such.
- Where the vibratory plate will not reach use a hand tamper or a block of wood and a hammer, compact corners and other hard to reach areas.
- All crushed stone aggregates are not created equal, when in doubt, do a test area.
- **GATOR STONE BOND XP** does work on sands, but sands are not considered as strong "structurally speaking" as a crushed stone mix with larger size stones like a 3/8 minus would have.
- **GATOR STONE BOND XP** may slightly darken the crushed stone mix.
- **GATOR STONE BOND XP** is not concrete, expect that some surface aggregates will become loose over time.
- In some instances a crack may appear, if the foundation is not well prepared.
- Slope the surface so water will run off.
- Form or taper the edges (if you choose to form, leave them in place when done).
- Allow 24 to 48 hours at a temperature above 60°F (16°C) for surface to cure.
- Do not apply **GATOR STONE BOND XP** if rain is expected within 48 hours.
- Please store **GATOR STONE BOND XP** container at above 32°F (0°C).
- **GATOR STONE BOND XP** is sold in Canada and USA.
- **GATOR STONE BOND** is only sold in the following states: California, Nevada, Texas, Arizona





**GATOR STONE BOND & XP
FOR PATHWAYS, PATIOS AND WALKWAYS**
TDS Revision Date (dd/mm/yyyy): 02/07/2019

Coverage:

Divide your coverage surface into sections to ensure a equal application of the product

GATOR STONE BOND & XP COVERAGE		
	RESIDENTIAL PEDESTRIAN	COMMERCIAL PEDESTRIAN
	ft²	ft²
1 U.S. Gal.	15	10

Packaging:	Product	Size	per Box	per Pallet
	GATOR STONE BOND	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR STONE BOND	18.9 L (5 U.S. gal.)		48 pails
	GATOR STONE BOND XP	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR STONE BOND XP	18.9 L (5 U.S. gal.)		48 pails

WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface and sub-surface preparation and product application. ALLIANCE DESIGNER PRODUCTS INC. agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then ALLIANCE DESIGNER PRODUCTS INC. agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC. IN ALL EVENTS, ALLIANCE DESIGNER PRODUCTS INC., SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, ALLIANCE DESIGNER PRODUCTS INC., EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.

SEE THE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com